



CLIMATE-SHIELD® ACRYLIC FLEX TAC BONDING COAT

DESCRIPTION

Climate-Shield® Acrylic Flex Tac is a bonding coat to be used over bitumen surfaces prior to the application of Climate-Shield® Roof or Climate-Shield® Exterior coating.

APPLICATION (1 Coat)

Apply Acrylic Flex Tac by roller or airless spray on a clean surface at approximately 6.2 m² per gallon (67 sq ft) in a one coat application. Allow drying time for a minimum of 12 hours before the application of Climate-Shield® Roof or Climate-Shield® Exterior coating.

Do not apply in freezing weather, or when precipitation is imminent.

CONSUMPTION

1 l / 1.6 m² in one application

DRYING TIME

To set: approx. 30 minutes

To through: min. 12 hours

Drying time at 25 ° C (77 ° F) and at 50% relative humidity

CLEANING

Clean tools and equipment with warm soapy water. Rinse with clean water; rinse the mineral distillates through a spray device to prevent corrosion and lubricate the material and seals.

PACKAGING

22,7 kg / 19 l

STORAGE

Store at a minimum of 5 ° C and maximum of 30 ° C

ATTENTION: Protect from frost !!!

COMBUSTIBILITY

Class I Non-flammable (water based) Unregulated

PRODUCT WARRANTY

10 years