



CLIMATE-SHIELD® METAL PRIMER

DESCRIPTION

Climate-Shield® Metal Primer is rust inhibitive, water based, high quality, 100% acrylic resin, corrosion resistant coating.

TYPICAL USES

It is used as a Primer / Base Coat on all rusty metal tanks & pipelines, water tanks, silos, storage bins, metal roofs, beams etc., surfaces, prior to the application of Climate-Shield® Roof Coat or Climate-Shield® Tank Shield.

SURFACE PREPARATION

Good cleaning of the metal must precede the Metal primer application. Surface must be cleaned of grease, oil, dirt and loose rust with a power sander or grinder, or wire brushing.

ADHESION

Very good adhesion to steel and iron surfaces, becomes part of the piece that is painted.

APPLICATION

Apply with brush, roller, or airless spray equipment.

THEORETICAL COVERAGE

14 – 23 m² / Gallon (150 – 250 sf / Gallon) Per Coat 3.7- 6.0 m² / Liter - Per Coat

*Minimum of 2 coats required

DRYING TIME

1 hour to touch (77 F & 50% relative humidity) 4 hours to re-coat.

PACKAGING

22,7 kg / 19 l

PRODUCT DATA

Solvent: Water

Flash Point: Non-Flammable (water based) DO NOT FREEZE

Percent Volatile by Volume: 62%

Weight by Gallon: 10.65 Lbs

V.O.C.: 0.31 Lbs/Gallon